

FUNI IN ACCIAIO

FC • anima tessile
WSC • anima metallica
IWRC • anima met. composta

fune per
Agricoltura
Industria

1



1 X 19 • EN 12385-10

FUNE SPIROIDALE IN ACCIAIO

	CODICE	Ø NOMINALE	PESO	CARICO DI ROTTURA minimo 1770 N/mm ²
	nr	mm	ca. Kg/m	kN (1 kN = 101,9716 kg)
1	FZB0100W019ST3AZ	1	0,005	0,93
2	FZB0125W019ST3AZ	1,25	0,008	1,46
3	FZB0150W019ST3AZ	1,5	0,011	2,10
4	FZB0200W019ST3AZ	2	0,019	3,73
5	FZB0250W019ST3AZ	2,5	0,030	5,82
6	FZB0300W019ST3AZ	3	0,044	8,38
7	FZB0350W019ST3AZ	3,5	0,059	11,41
8	FZB0400W019ST3AZ	4	0,078	14,91
9	FZB0500W019ST3AZ	5	0,121	23,29
10	FZB0600W019ST3AZ	6	0,175	33,54
11	FZB0700W019ST3AZ	7	0,238	45,65
12	FZB0800W019ST3AZ	8	0,310	59,63
13	FZB0900W019ST3AZ	9	0,393	75,46
14	FZB1000W019ST3AZ	10	0,485	93,17
15	FZB1100W019ST3AZ	11	0,587	112,73
16	FZB1200W019ST3AZ	12	0,698	134,16
17	FZB1400W019ST3AZ	14	0,951	182,61
18	FZB1600W019ST3AZ	16	1,242	238,51
19	FZB1800W019ST3AZ	18	1,571	301,86
20	FZB2000W019ST3AZ	20	1,940	372,66