

## FUNI IN ACCIAIO

FC • anima tessile  
WSC • anima metallica  
IWRC • anima met. composta

3



**6 X 19 + FC • EN 12385-4**  
ACCIAIO

fune per  
**Industria**

	CODICE	Ø NOMINALE	PESO	CARICO DI ROTTURA minimo 1770 N/mm <sup>2</sup>
	nr	mm	ca. Kg/m	kN (1 kN = 101,9716 kg)
1	FZB0300F114ST3AZ	3	0,031	4,89
2	FZB0400F114ST3AZ	4	0,055	8,69
3	FZB0500F114ST3AZ	5	0,087	13,58
4	FZB0600F114ST3AZ	6	0,125	19,56
5	FZB0700F114ST3AZ	7	0,170	26,93
6	FZB0800F114ST3AZ	8	0,221	34,78
7	FZB0900F114ST3AZ	9	0,280	44,01
8	FZB1000F114ST3AZ	10	0,346	54,34
9	FZB1100F114ST3AZ	11	0,419	65,75
10	FZB1200F114ST3AZ	12	0,498	78,25
11	FZB1400F114ST3AZ	14	0,678	106,5
12	FZB1600F114ST3AZ	16	0,886	139,11
13	FZB1800F114ST3AZ	18	1,121	176,06
14	FZB2000F114ST3AZ	20	1,384	217,36

2015 | [trentinorope.com](http://trentinorope.com)

© 2014-2015 Copyright TrentinoRope Srl | P.IVA IT02315980223