


FUNI IN ACCIAIO

FC • anima tessile
WSC • anima metallica
IWRC • anima met. composta

fune per
Industria

5



6 X 19S + FC • EN 12385-4
FUNE IN ACCIAIO

	CODICE	Ø NOMINALE	PESO	CARICO DI ROTTURA minimo 1770 N/mm ²
	nr	mm	ca. Kg/m	kN (1 kN = 101,9716 kg)
1	FZB0600F114SE3AZ	6	0,129	21,03
2	FZB0700F114SE3AZ	7	0,176	28,62
3	FZB0800F114SE3AZ	8	0,230	37,38
4	FZB0900F114SE3AZ	9	0,291	47,31
5	FZB1000F114SE3AZ	10	0,359	58,41
6	FZB1100F114SE3AZ	11	0,434	70,68
7	FZB1200F114SE3AZ	12	0,517	84,11
8	FZB1300F114SE3AZ	13	0,607	98,71
9	FZB1400F114SE3AZ	14	0,704	114,48
10	FZB1600F114SE3AZ	16	0,919	149,53
11	FZB1800F114SE3AZ	18	1,163	189,25
12	FZB2000F114SE3AZ	20	1,436	233,64

2015 | trentinorope.com

© 2014-2015 Copyright TrentinoRope Srl | P.IVA IT02315980223