

FUNI IN ACCIAIO

FC • anima tessile
WSC • anima metallica
IWRC • anima met. composta

fune per
Industria

6



6 X 36WS + FC • EN 12385-4
FUNE IN ACCIAIO

	CODICE	Ø NOMINALE	PESO	CARICO DI ROTTURA minimo 1770 N/mm ²
	nr	mm	ca. Kg/m	kN (1 kN = 101,9716 kg)
1	FZB0600F216WS3AZ	6	0,132	21,03
2	FZB0800F216WS3AZ	8	0,235	37,38
3	FZB1000F216WS3AZ	10	0,367	58,41
4	FZB1200F216WS3AZ	12	0,529	84,11
5	FZB1400F216WS3AZ	14	0,719	114,48
6	FZB1600F216WS3AZ	16	0,940	149,53
7	FZB1800F216WS3AZ	18	1,189	189,25
8	FZB2000F216WS3AZ	20	1,468	233,64
9	FZB2200F216WS3AZ	22	1,776	282,70
10	FZB2400F216WS3AZ	24	2,114	336,44
11	FZB2600F216WS3AZ	26	2,481	394,85
12	FZB2800F216WS3AZ	28	2,877	457,93

2015 | trentinorope.com

© 2014-2015 Copyright TrentinoRope Srl | P.IVA IT02315980223