


FUNI IN ACCIAIO

FC • anima tessile
WSC • anima metallica
IWRC • anima met. composta

7



6 X 36WS + IWRC • EN 12385-4
FUNE IN ACCIAIO

fune per
Industria

	CODICE	Ø NOMINALE	PESO	CARICO DI ROTTURA minimo 1770 N/mm ²
	nr	mm	ca. Kg/m	kN (1 kN = 101,9716 kg)
1	FZB0600I216WS3AZ	6	0,147	22,68
2	FZB0800I216WS3AZ	8	0,262	40,33
3	FZB1000I216WS3AZ	10	0,409	63,01
4	FZB1200I216WS3AZ	12	0,589	90,74
5	FZB1400I216WS3AZ	14	0,802	123,50
6	FZB1600I216WS3AZ	16	1,047	161,31
7	FZB1800I216WS3AZ	18	1,325	204,16
8	FZB2000I216WS3AZ	20	2,636	252,05
9	FZB2200I216WS3AZ	22	2,978	304,98
10	FZB2400I216WS3AZ	24	2,360	362,95
11	FZB2600I216WS3AZ	26	2,765	425,96
12	FZB2800I216WS3AZ	28	3,207	494,01

2015 | trentinorope.com

© 2014-2015 Copyright TrentinoRope Srl | P.IVA IT02315980223