

## FUNI IN ACCIAIO

FC • anima tessile  
WSC • anima metallica  
IWRC • anima met. composta

fune per

**Industria**

8



**19 X 7 • EN 12385-4**

FUNE ANTIGIRO IN ACCIAIO

	CODICE	Ø NOMINALE	PESO	CARICO DI ROTTURA minimo 1960 N/mm <sup>2</sup>
	nr	mm	ca. Kg/m	kN (1 kN = 101,9716 kg)
1	FZB0300W133AN4AZ	3	0,036	5,79
2	FZB0400W133AN4AZ	4	0,064	10,29
3	FZB0500W133AN4AZ	5	0,100	16,07
4	FZB0600W133AN4AZ	6	0,144	23,14
5	FZB0700W133AN4AZ	7	0,197	31,50
6	FZB0800W133AN4AZ	8	0,257	41,14
7	FZB0900W133AN4AZ	9	0,325	52,07
8	FZB1000W133AN4AZ	10	0,401	64,29
9	FZB1100W133AN4AZ	11	0,485	77,79
10	FZB1200W133AN4AZ	12	0,577	92,57
11	FZB1300W133AN4AZ	13	0,678	108,65
12	FZB1400W133AN4AZ	14	0,786	126,00
13	FZB1600W133AN4AZ	16	1,027	164,58
14	FZB1800W133AN4AZ	18	1,299	208,29

2015 | [trentinorope.com](http://trentinorope.com)

© 2014-2015 Copyright TrentinoRope Srl | P.IVA IT02315980223