

FUNI IN ACCIAIO

FC • anima tessile
WSC • anima metallica
IWRC • anima met. composta

10



1 X 19 • EN 12385-10 • AISI 316

FUNE SPIROIDALE IN ACCIAIO INOX

fune per

Industria

	CODICE	Ø NOMINALE	PESO	CARICO DI ROTTURA minimo 1570 N/mm ²
	nr	mm	ca. Kg/m	kN (1 kN = 101,9716 kg)
1	FX60100W019ST2AZ	1	0,005	0,83
2	FX60125W019ST2AZ	1,25	0,008	1,29
3	FX60150W019ST2AZ	1,5	0,011	1,86
4	FX60200W019ST2AZ	2	0,019	3,31
5	FX60250W019ST2AZ	2,5	0,030	5,16
6	FX60300W019ST2AZ	3	0,044	7,44
7	FX60350W019ST2AZ	3,5	0,059	10,12
8	FX60400W019ST2AZ	4	0,078	13,22
9	FX60500W019ST2AZ	5	0,122	20,66
10	FX60600W019ST2AZ	6	0,175	29,75
11	FX60700W019ST2AZ	7	0,238	40,49
12	FX60800W019ST2AZ	8	0,310	52,89
13	FX61000W019ST2AZ	10	0,485	82,64
14	FX61200W019ST2AZ	12	0,698	119,00
15	FX61400W019ST2AZ	14	0,951	161,97
16	FX61600W019ST2AZ	16	1,242	211,56

2015 | trentinorope.com

© 2014-2015 Copyright TrentinoRope Srl | P.IVA IT02315980223