


## FUNI IN ACCIAIO

FC • anima tessile  
WSC • anima metallica  
IWRC • anima met. composta

11



**6 X 7 + WSC • EN 12385-4 • AISI 316**

FUNE IN ACCIAIO INOX

funi per

**Industria**

	CODICE	Ø NOMINALE	PESO	CARICO DI ROTTURA minimo 1570 N/mm <sup>2</sup>
	nr	mm	ca. Kg/m	kN (1 kN = 101,9716 kg)
1	FX60100W042ST2AZ	1	0,004	0,56
2	FX60150W042ST2AZ	1,5	0,009	1,27
3	FX60200W042ST2AZ	2	0,015	2,25
4	FX62500W042ST2AZ	2,5	0,024	3,52
5	FX60300W042ST2AZ	3	0,035	5,07
6	FX60400W042ST2AZ	4	0,061	9,02
7	FX60500W042ST2AZ	5	0,096	14,09
8	FX60600W042ST2AZ	6	0,138	20,29
9	FX60700W042ST2AZ	7	0,188	27,62
10	FX60800W042ST2AZ	8	0,246	36,07
11	FX61000W042ST2AZ	10	0,384	56,36
12	FX60100W042ST2AZ	12	0,553	81,16

2015 | [trentinorope.com](http://trentinorope.com)

© 2014-2015 Copyright TrentinoRope Srl | P.IVA IT02315980223