

## FUNI IN ACCIAIO

FC • anima tessile  
WSC • anima metallica  
IWRC • anima met. composta

12



**6 X 19 + WSC • EN 12385-4 • AISI 316**

FUNE IN ACCIAIO INOX

fune per  
**Industria**

CODICE		Ø NOMINALE	PESO	CARICO DI ROTTURA minimo 1570 N/mm <sup>2</sup>
nr		mm	ca. Kg/m	kN (1 kN = 101,9716 kg)
1	FX60200W114ST2AZ	2	0,015	2,27
2	FX60250W114ST2AZ	2,5	0,024	3,55
3	FX60300W114ST2AZ	3	0,034	5,12
4	FX60400W114ST2AZ	4	0,061	9,09
5	FX60500W114ST2AZ	5	0,095	14,21
6	FX60600W114ST2AZ	6	0,137	20,46
7	FX60700W114ST2AZ	7	0,187	27,85
8	FX60800W114ST2AZ	8	0,244	36,37
9	FX61000W114ST2AZ	10	0,381	56,83
10	FX61200W114ST2AZ	12	0,549	81,84
11	FX61400W114ST2AZ	14	0,747	111,39
12	FX61600W114ST2AZ	16	0,976	145,50
13	FX61800W114ST2AZ	18	1,234	184,14
14	FX62000W114ST2AZ	20	1,524	227,34

2015 | [trentinorope.com](http://trentinorope.com)

© 2014-2015 Copyright TrentinoRope Srl | P.IVA IT02315980223