



GOLFARO ZINCATO MASCHIO DIN 580 C15E

COEFFICIENTE DI SICUREZZA 6:1

A filetto	B mm	C mm	D mm	F mm	G mm	E mm	H mm	WLL1 kg	PESO kg	WLL2 kg	WLL3 kg	WLL4 kg	WLL5 kg
M6	6	14	6	14	27	11	26	90	0,017	90	90	60	135
M8	8,5	20	8	20	36	13	36	140	0,05	140	140	95	210
M10	10	25	10	25	45	17	45	230	0,09	230	230	160	345
M12	11	30	12	30	53	20,5	54	340	0,16	340	340	240	510
M14	11	30	12	30	53	20,5	54	480	0,16	480	480	335	720
M16	13	35	14	35	62	27	63	700	0,24	700	700	495	1050
M18	13	35	14	35	62	27	63	930	0,24	930	930	655	1395
M20	16	40	16	40	71	30	72	1200	0,36	1200	1200	845	1800
M22	16	40	16	40	71	30	72	1450	0,36	1450	1450	1025	2175
M24	20	50	20	50	90	36	90	1800	0,72	1800	1800	1270	2700
M27	21	55	21	55	100	41	96	2400	0,845	2400	2400	1695	3600
M30	25	65	24	60	109	45	108	3200	1,32	3200	3200	2260	4800

