


CAMPANELLA • GRADO 100




∟ Ø mm	∧ Ø mm	D mm	T mm	W mm	S mm	PESO kg	WLL 0°-45° kg
6+7	6	13	110	60	10	0,34	2300
8	7	16,5	110	60	14	0,53	3500
10	8	19	135	75	14	0,92	5000
13	10	23	160	90	17	1,6	7600
16	13	27	180	100	20	2,46	10000
19	16	33	200	110	26	4,14	14000
22	19	36	260	140	-	6,22	25100

COEFFICIENTE DI SICUREZZA 4:1

- SU RICHIESTA DISPONIBILE SENZA SCHIACCIATURA
- SU RICHIESTA DISPONIBILE CON DIMENSIONI MAGGIORATE

COMPLESSIVO • GRADO 100



∧ Ø mm	E mm	D mm	T mm	W mm	T1 mm	W1 mm	S mm	PESO kg	WLL 0°-45° kg
6	189	19	135	75	54	25	10	1,26	4200
7+8	230	23	160	90	70	34	14	2,32	7600
10	265	27	180	100	85	40	14	3,68	9600
13	315	33	200	110	115	50	17	6,46	14000
16	400	36	260	140	140	65	20	10,06	21200
19+20	500	50	350	190	150	70	26	22,87	34100
22	520	50	350	190	170	75	-	24,79	40000

COEFFICIENTE DI SICUREZZA 4:1