



## FUNE IN ACCIAIO

# 6 X 7 + WSC • EN 12385-4

WSC = anima metallica

CODICE nr	Ø mm ca.	PESO Kg/m	CARICO DI ROTTURA MIN. [MBL] R1770 N/mm <sup>2</sup> • kN (1 kN = 101,97 kg)
FZB0100W042ST3AZ	1	0,004	0,64
FZB0150W042ST3AZ	1,5	0,009	1,43
FZB0200W042ST3AZ	2	0,015	2,54
FZB0250W042ST3AZ	2,5	0,024	3,97
FZB0300W042ST3AZ	3	0,035	5,72
FZB0400W042ST3AZ	4	0,061	10,17
FZB0500W042ST3AZ	5	0,096	15,89
FZB0600W042ST3AZ	6	0,138	22,88
FZB0700W042ST3AZ	7	0,188	31,14
FZB0800W042ST3AZ	8	0,246	40,67
FZB1000W042ST3AZ	10	0,384	63,54
FZB1200W042ST3AZ	12	0,553	91,50

- FUNE DISPONIBILE CON ZINCATURA CLASSE B, CLASSE A E ZINCO / ALLUMINIO
- FUNE DISPONIBILE ANCHE CON ANIMA TESSILE