


EN818-2 • GRADO 80 • CATENA

D mm	P mm	Li/min mm	Le/max mm	PESO kg/m	WLL kg
6	18	7,8	22,2	0,8	1120
7	21	9,1	25,9	1,1	1500
8	24	10,4	29,6	1,4	2000
10	30	13	37	2,2	3150
13	39	16,9	48,1	3,8	5300
16	48	20,8	59,2	5,7	8000
18	54	23,4	66,6	7,3	10000
19	57	24,7	70,3	8,1	11200
20	60	26	74	9	12500



COEFFICIENTE DI SICUREZZA 4:1

CATENA	1 BRACCIO	2 BRACCIA		3/4 BRACCIA	
		$0^\circ < \beta \leq 45^\circ$	$0^\circ < \beta \leq 60^\circ$	$0^\circ < \beta \leq 45^\circ$	$0^\circ < \beta \leq 60^\circ$
\emptyset mm	kg	kg		kg	
6	1.120	1.600	1.120	2.360	1.700
7	1.500	2.120	1.500	3.150	2.240
8	2.000	2.800	2.000	4.250	3.000
10	3.150	4.250	3.150	6.700	4.750
13	5.300	7.500	5.300	11.200	8.000
16	8.000	11.200	8.000	17.000	11.800
18	10.000	14.000	10.000	21.200	15.000
19	11.200	16.000	11.200	23.600	17.000
20	12.500	17.000	12.500	26.500	19.000

