


## CAMPANELLA • GRADO 80

$\perp$ Ø mm	$\wedge$ Ø mm	D mm	T mm	W mm	S mm	PESO kg	WLL 0°-45° kg
7	6	13	110	60	10	0,34	1600
8	7	16	110	60	14	0,53	2120
10	8	18	135	75	14	0,92	3150
13	10	22	160	90	17	1,6	5300
16	13	26	180	100	20	2,46	8000
18	16	32	200	110	26	4,14	11200




COEFFICIENTE DI SICUREZZA 4:1

- SU RICHIESTA DISPONIBILE SENZA SCHIACCIATURA
- SU RICHIESTA DISPONIBILE CON DIMENSIONI MAGGIORATE

## COMPLESSIVO • GRADO 80

$\uparrow$ Ø mm	D1 mm	P1 mm	L1 mm	D2 mm	P2 mm	L2 mm	SxX mm	PESO kg	WLL 0°-45° kg
6	19	135	75	13	60	38	10x25	1,32	2360
7	19	135	75	13	60	38	10x25	1,32	3150
8	23	160	90	16,5	70	34	14x25	2,32	4250
10	27	180	100	18,5	85	60	14x35	3,52	6700
13	33	200	110	23	115	50	17x35	6,26	11200
16	36	260	140	27	140	65	20x45	9,86	17000
18	45	340	180	33	150			18,92	21200
20	50	350	190	33	150			22,65	26500



COEFFICIENTE DI SICUREZZA 4:1