



TENDITORE ALTA RESISTENZA ZINCATO FORCELLA-FORCELLA

COEFFICIENTE DI SICUREZZA 5:1

MISURA pollici	ØB1 mm	C mm	D mm	E mm	F mm	L min mm	L max mm	WFL kg	PESO kg
3/8x6	7,8	21,5	12	152	183	258	410	540	0,37
1/2x6	9,6	26	16	152	193	306	458	1000	0,43
1/2x9	9,6	26	16	229	269	368	597	1000	0,79
1/2x12	9,6	26	16	305	346	456	761	1000	1,1
5/8x6	12,5	32,5	18	152	202	346	498	1590	1,18
5/8x9	12,5	32,5	18	229	279	401	630	1590	1,47
3/4x6	15,5	38	24	152	213	369	521	2360	1,92
3/4x9	15,5	38	24	229	289	432	660	2360	2,31
3/4x12	15,5	38	24	305	366	519	824	2360	2,72
3/4x18	15,5	38	24	457	518	671	1128	2360	3,7
7/8x12	18,6	42,5	27,5	305	376	542	847	3270	3,71
7/8x18	18,6	42,5	27,5	457	528	713	1170	3270	4,65
1x6	22	50,5	30,5	152	234	425	577	4540	3,86
1x12	22	50,5	30,5	305	386	577	882	4540	5,44
1x18	22	50,5	30,5	457	538	751	1208	4540	6,46
1.1/4x12	29	71,5	44	305	385	644	948	6900	9,75
1.1/4x18	29	71,5	44	457	537	796	1253	6900	11
1.1/4x24	29	71,5	44	610	689	948	1558	6900	12,7
1.1/2x12	35	71	52	305	401	675	942	9710	17,3
1.1/2x18	35	71	52	457	553	825	1282	9710	19,4
1.1/2x24	46	71	52	610	706	979	1589	9710	21,6
1.3/4x18	41	86	59,5	457	577	938	1316	12700	30,9

© TrentinoRope S.r.l.