



TENDITORE ALTA RESISTENZA ZINCATO OCCHIO-OCCHIO

COEFFICIENTE DI SICUREZZA 5:1

MISURA pollici	ØB mm	D mm	E mm	F mm	L min mm	L max mm	WFL kg	PESO kg
3/8x6	9,5	13,5	152	183	292	444	540	0,34
1/2x6	11,5	18	152	193	320	467	1000	0,43
1/2x9	11,5	18	229	269	408	637	1000	0,83
5/8x9	13,5	21,5	229	279	449	677	1590	1,42
3/4x6	16,5	25,5	152	213	410	552	2360	1,66
3/4x9	16,5	25,5	229	289	492	721	2360	2,09
3/4x12	16,5	25,5	305	366	560	856	2360	2,54
3/4x18	16,5	25,5	457	518	710	1160	2360	3,2
7/8x12	19,5	32,5	305	376	592	897	3270	3,67
7/8x18	19,5	32,5	457	528	754	1211	3270	4,55
1x6	23,5	36,6	152	234	507	660	4540	4,23
1x12	23,5	36,6	305	386	660	964	4540	5,41
1.1/4x12	29,5	46,5	305	385	719	1024	6900	8,62
1.1/4x18	29,5	46,5	457	537	872	1329	6900	10,4
1.1/4x24	29,5	46,5	610	689	1024	1634	6900	12,3
1.1/2x12	32	54,5	305	401	756	1023	9710	13,5
1.1/2x18	32	54,5	457	533	916	1370	9710	16
1.3/4x18	38	60,5	457	577	1020	1396	12700	24,7