



FUNE IN ACCIAIO

1 X 19 • EN 12385-10

SPIROIDALE

CODICE n	Ø mm ca.	PESO Kg/m	CARICO DI ROTTURA MIN. [MBL] R1770 N/mm ² • kN (1 kN = 101,97 kg)
FZB0100W019ST3AZ	1	0,005	0,93
FZB0125W019ST3AZ	1,25	0,008	1,46
FZB0150W019ST3AZ	1,5	0,011	2,10
FZB0200W019ST3AZ	2	0,019	3,73
FZB0250W019ST3AZ	2,5	0,030	5,82
FZB0300W019ST3AZ	3	0,044	8,38
FZB0350W019ST3AZ	3,5	0,059	11,41
FZB0400W019ST3AZ	4	0,078	14,91
FZB0500W019ST3AZ	5	0,121	23,29
FZB0600W019ST3AZ	6	0,175	33,54
FZB0700W019ST3AZ	7	0,238	45,65
FZB0800W019ST3AZ	8	0,310	59,63
FZB1000W019ST3AZ	10	0,485	93,17
FZB1200W019ST3AZ	12	0,698	134,16
FZB1400W019ST3AZ	14	0,951	182,61

- FUNE DISPONIBILE CON ZINCATURA CLASSE B, CLASSE A E ZINCO/ALLUMINIO

